

PM11



This instrument is a pocket type digital multimeter designed for the measurement of low-voltage circuit.

This is used at small communications equipments, home electric appliances, voltage of lump line, and measurement of various types of batteries.

- •4000 count
- •0.8% best accuracy
- Analog bar graph
- Compact storage of test leads
- •Test lead can be snapped into a fixed position atop the case.

SPECIFICATIONS

	Measuring range		Best accuracy	Resolution	Input impedance			
DCV	400m/4/40/400/500V		±(0.8%+4)	0.1mV	DCV:			
ACV 4/40/400/500)V	±(2.3%+8)	0.001V	10M~100MO			
Resistance 400/4k/40k/4		100k/4M/40MΩ	±(2.0%+4)	0.1Ω	ACV:			
Continuity	Buzzer sounds at less than 35Ω. Open		voltage : approx.	10M~11MO				
Diode test	Open voltag	je : approx. 3V			I OIVI - I I IVIZZ			
Measuring method		Dual integration						
Display		Counter approx. 4000 counts max. Bar graph max. 40 segments						
Range selection		Auto range						
Over display		"OL" is displayed						
Polarity		Automatic selection(only " - " is displayed when negative voltage is inputted.)						
Battery low warning		Battery() mark lights when the internal battery's power is low.						
Sampling rate		Approx. 1.3 times/sec(numeral display)						
		Approx. 13 times/sec(bar graph)						
Operating temperature / humidity		0~40°C, 80%RH(Max)						
Storage temperature / humidity		-10°C~50°C, below 70%RH No condensation						
Environmental condition		Altitude 2000m or below, pollution degree II						
Power consumption		3.5mW(at DCV)						
Bandwidth		45∼1kHz						
Battery		Button battery LR44 x 2						
Size / Mass		H117 x W76 x D18mm / 117g						
Standard accessories included		Instruction Manual						



A battery for monitoring has been installed prior to shipment from the factory. It may be discharged before the expiration of the described battery life. This battery is used to check the functions and performance of the product. Specifications and external appearance of the product described above may be revised for modification without prior notice.

sanwa

SANWA ELECTRIC INSTRUMENT CO., LTD.

Dempa Bldg, 4-4 Sotokanda 2-Chome, Chiyoda-Ku, Tokyo 101-0021 Japan Tel:+81-3-3251-0941 Fax:+81-3-3256-9740

www.sanwa-meter.co.jp

ח	ist	rih	111	e	ч	hν